

 Close this window

MSDS

Common Name: LIQUIFIED PETROLEUM GAS OR PROPANE (0916-0004)

Manufacturer: VICTOR EQUIPMENT

MSDS Revision Date: 3/1/2007

Grainger Item Number(s): 4PE97, 5UX34

**Manufacturer Model
Number(s):**

MSDS Table of Contents

Click the desired link below to jump directly to that section in the MSDS.

[SECTION I - MATERIAL IDENTIFICATION](#)
[SECTION II - HAZARDOUS INGREDIENTS](#)
[SECTION III - HAZARDS IDENTIFICATIONS](#)
[SECTION IV - FIRST AID MEASURES](#)
[SECTION V - FIRE FIGHTING MEASURES](#)
[SECTION VI - ACCIDENTAL RELEASE MEASURES](#)
[SECTION VII - HANDLING AND STORAGE](#)
[SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION](#)
[SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES](#)
[SECTION X - STABILITY AND REACTIVITY](#)
[SECTION XI - TOXICOLOGICAL INFORMATION](#)
[SECTION XII - ECOLOGICAL INFORMATION](#)
[SECTION XIII - DISPOSAL CONSIDERATIONS](#)
[SECTION XIV - TRANSPORTATION INFORMATION](#)
[SECTION XV - REGULATORY INFORMATION](#)
[SECTION XVI - OTHER INFORMATION](#)

PROPANE FUEL

THERMADYNE

VICTOR (R*)

MATERIAL SAFETY DATA SHEET

CHEMTREC PHONE NO.: (800) 424-9300

VICTOR EQUIPMENT COMPANY:
2800 AIRPORT ROAD
DENTON, TEXAS 76207
(940) 566-2000

FAX: (940) 381-1265

DATE PREPARED: JANUARY 1, 1991

DATE REVISED: MARCH 1, 2007

FORM NUMBER: 0056-1297

CORE PART NO: 0916-0004

THIS MSDS IS BASED ON AIR/FUEL OR OXY/FUEL PROCESS.

THERE MAY BE OTHER CAUTIONS FOR ELECTRIC PROCESS.

MATERIAL SAFETY DATA SHEET

SECTION I - MATERIAL IDENTIFICATION



PRODUCT NAME: LIQUIFIED PETROLEUM GAS OR PROPANE (0916-0004)

PRODUCT USE: HEATING FUEL

SECTION II - HAZARDOUS INGREDIENTS



OSHA HAZARDOUS COMPONENTS
(29 CFR 1910.1200)

EXPOSURE LIMITS: 8 HR. TWA
OSHA PEL ACGIH TLV

PROPANE
(CAS #: 74-98-6)

100 PPM NOT LISTED

SECTION III - HAZARDS IDENTIFICATIONS



EMERGENCY OVERVIEW:

FLAMMABLE GAS. MAY CAUSE FLASH FIRE OR EXPLOSION. CONTENTS UNDER PRESSURE.
HARMFUL IF INHALED.

POTENTIAL HEALTH EFFECTS:

INHALATION:

MAY CAUSE HEADACHES AND DIZZINESS. MAY CAUSE ASPHYXIATION IN HIGH
CONCENTRATIONS. PROLONGED INHALATION MAY BE HARMFUL.

EYE CONTACT: DIRECT CONTACT WITH LIQUIFIED GAS CAN RESULT IN EYE BURNS.

SKIN CONTACT: NO HAZARD IN NORMAL INDUSTRIAL USE.

INGESTION: INGESTION NOT LIKELY, PRODUCT IS A GAS AT ROOM TEMPERATURE.

CHRONIC: UNKNOWN.

CARCINOGENICITY:

LISTED IN NTP?: NO

IARC?: NO

OSHA REGULATED?: NO

SECTION IV - FIRST AID MEASURES



INHALATION:

REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION AND/OR
GIVE OXYGEN BY TRAINED PERSONNEL. SEEK MEDICAL ATTENTION.

EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER. GET MEDICAL ATTENTION IF

IRRITATION PERSISTS.

SKIN CONTACT:

WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

INGESTION: NO EMERGENCY CARE ANTICIPATED.

SECTION V - FIRE FIGHTING MEASURES



FLASHPOINT (METHOD): -156 DEG. F (ND)

FLAMMABLE LIMITS:

LOWER: 2.3

UPPER: 9.5

AUTOIGNITION TEMPERATURE: 874 DEG. F

GENERAL HAZARD:

FLAMMABLE GAS. CAN READILY FORM EXPLOSIVE MIXTURES AT OR ABOVE THE FLASHPOINT. FLASHBACK ALONG VAPOR TRAIL POSSIBLE.

FIRE FIGHTING INSTRUCTIONS:

EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE. DO NOT EXTINGUISH A GAS FIRE UNLESS EFFECTIVE IMMEDIATE SHUT-OFF OF GAS FLOW IS POSSIBLE. EXPLOSIVE VAPORS COULD FORM. AS IN ANY FIRE, WEAR SELF-CONTAINED BREATHING APPARATUS (PRESSURE-DEMAND, MSHA/NIOSH APPROVED OR EQUIVALENT) AND FULL PROTECTIVE GEAR.

EXTINGUISHING MEDIA:

DO NOT EXTINGUISH. USE WATER TO COOL CONTAINERS. INCREASE VENTILATION TO PREVENT FLAMMABLE AIR MIXTURE.

HAZARDOUS COMBUSTION PRODUCTS: SMOKE, OXIDES OF CARBON.

SECTION VI - ACCIDENTAL RELEASE MEASURES



ELIMINATE ALL IGNITION SOURCES INCLUDING INTERNAL COMBUSTION ENGINES AND POWER TOOLS. VENTILATE AREA. ISOLATE HAZARD AREA. KEEP UNNECESSARY AND UNPROTECTED PERSONNEL FROM ENTERING. AVOID BREATHING VAPORS. AVOID CONTACT WITH EYES, SKIN, AND CLOTHING.

SECTION VII - HANDLING AND STORAGE



USE SPARK-PROOF TOOLS AND EXPLOSION PROOF EQUIPMENT. GROUND AND BOND CONTAINERS WHEN TRANSFERRING MATERIAL. DO NOT REUSE THIS CONTAINER. "EMPTY" CONTAINERS RETAIN PRODUCT RESIDUE (LIQUID AND/OR VAPOR) AND CAN BE DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. EMPTY DRUMS SHOULD BE COMPLETELY DRAINED, PROPERLY SEALED AND PROMPTLY RETURNED TO A DRUM RECONDITIONER, OR DISPOSED OF PROPERLY. KEEP AWAY FROM HEAT, SPARKS AND FLAME. STORE IN A COOL DRY PLACE.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION



ENGINEERING CONTROLS:

USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS.

PERSONAL PROTECTION:

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE.

PROTECTIVE CLOTHING:

WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES) AND A FACE SHIELD.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE: 7600 MMHg @ 80 DEG. C

VAPOR DENSITY (AIR=1): 1.5

SPECIFIC GRAVITY: 0.50

EVAPORATION RATE (n-BUTYL ACETATE=1): NA

SOLUBILITY IN WATER: NEGLIGIBLE

pH: NA

FREEZING POINT: -306 DEG. F

BOILING POINT: -44 DEG. F

APPEARANCE & ODOR:

COLORLESS GAS WITH NO ODOR. IF ODORIZED, WILL HAVE ROTTEN EGG ODOR.

SECTION X - STABILITY AND REACTIVITY

GENERAL: STABLE

INCOMPATIBLE MATERIALS: OXIDIZERS

CONDITIONS TO AVOID: HEAT, IGNITION SOURCES.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SECTION XI - TOXICOLOGICAL INFORMATION

NO TOXICITY DATA DETERMINED.

SECTION XII - ECOLOGICAL INFORMATION

NOT APPLICABLE.

SECTION XIII - DISPOSAL CONSIDERATIONS

DO NOT ATTEMPT TO DISPOSE WASTE OR UNUSED MATERIAL. RETURN IN CONTAINER

PROPERLY LABELED, WITH VALVE PROTECTION CAP IN PLACE TO THE SUPPLIER FOR PROPER DISPOSAL. CLASSIFICATION REQUIRED BEFORE DISPOSAL. MATERIAL IS CLASSIFIED AS IGNITABLE WITH A RCRA D001 HAZARDOUS WASTE NUMBER. FOLLOW ALL FEDERAL, STATE AND LOCAL REQUIREMENTS.

SECTION XIV - TRANSPORTATION INFORMATION



PROPER SHIPPING NAME: LIQUIFIED PETROLEUM GAS, 2.1

HAZARD CLASS: FLAMMABLE GAS (2.1)

IDENTIFICATION NUMBER: UN 1978

DOT EMERGENCY GUIDE #: 22

REPORTABLE QUANTITY (RQ): 2,000,000 POUNDS (PROPANE) IN A SINGLE CONTAINER.

SECTION XV - REGULATORY INFORMATION



TSCA (TOXIC SUBSTANCE CONTROL ACT):
ALL COMPONENTS ARE LISTED ON THE TSCA INVENTORY.

CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT):
2,000,000 POUNDS. WE RECOMMEND YOU CONTACT LOCAL AUTHORITIES FOR OTHER REPORTING REQUIREMENTS.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):
311/312 HAZARD CATEGORIES: ACUTE, IGNITABLE, SUDDEN RELEASE OF PRESSURE.
313 REPORTABLE INGREDIENTS: NONE

SECTION XVI - OTHER INFORMATION



PREPARED BY:
TALEM, INC. - TECHNICAL SERVICES DIVISION: (817) 335-1186

FOOTNOTES:

NA - NOT APPLICABLE
NE - DATA NOT ESTABLISHED
CS - CANCER SUSPECT AGENT
OX - OXIDIZER
ND - NO DATA
COR - CORROSIVE
CALC - CALCULATED
EST - ESTIMATED
STEL - SHORT TERM EXPOSURE LIMIT
TLV - THRESHOLD LIMIT VALUE
PEL - PERMISSIBLE EXPOSURE LIMIT
TWA - TIME WEIGHTED AVERAGE, 8 HOURS

THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE. NEITHER THE SELLER NOR PREPARER MAKES ANY WARRANTIES, EXPRESS OR IMPLIED, CONCERNING THE INFORMATION PRESENTED.